

**General Data**

Model:	ALPHA V 4 M
Code:	2000262
Series:	Alpha V
Weight [Kg]	19.00
Submersible pump for sewage with suspended solids	

**Hydraulic**

Impeller Type:	-
Delivery DN [mm]:	G 2"
Input DN [mm]:	50
Free Passage [mm]:	45
Impeller Ø [mm]:	113
Max Pump Efficiency [%]:	0.0
Global Efficiency [%]:	-0.07
Head [m]:	8.20
Flow [m <sup>3</sup> /h]:	14.40

*Tolerance according to ISO 9906:2012 3B2*

**Features**

Upper Meccanical seal:	Lips seal
Lower Meccanical Seal:	Silicon Carbide/Ceramic/Viton
Upper Bearing:	Single raw ball bearing
Lower Bearing:	Single raw ball bearing
IP Protection:	IP68
Motor protection:	present
Humidity sensor:	not present
ATEX:	not present
Applied Paint:	Two component water-based paint
Cable Length [m]:	10
Lubricating Oil:	-
Oil Quantity [Kg]:	0.00

**Materials**

Pump:	-
Impeller:	-
Motor shaft:	-
Cooling Jacket:	Not available
Screw:	Stainless steel A2-70
Cable:	H07RN8F

**Pumped Liquid**



Pumped Liquid:	Sewage
Density [Kg/dm <sup>3</sup> ]:	1.1
pH:	2023-10-06
Temperature Range:	0-40°C

**Installation**

Maximum depth of immersion [m]:	20
Cooling Type:	The cooling of the motor is ensured by the surrounding liquid
Installation:	
Floating on board machine:	not present



Attention: pictures for illustrative purposes




$\eta$  global [%]



**Motor**

Motor code:	3520160210
Power P1 [kW]:	1.70
Power P2 [kW]:	1.10
Phases:	1
Frequency [Hz]:	50
Tension [V]:	230
Nominal current [A]:	7.6
Starting current [%]:	308.0
Power Factor:	0.98
R.P.M.:	2850
Starting:	D.O.L
Capacitor [ $\mu$ F]:	30.0
Insulation Class:	F 155°C
Service type:	S2
Max Efficiency [%]:	74.80
Max Efficiency at full load [%]:	72.9
Efficiency at $\frac{3}{4}$ load [%]:	74.0
Efficiency at $\frac{1}{2}$ load [%]:	73.5
Efficiency class:	-

**Wiring diagrams**

Dimensions drawing

